



HYDRAULIC PULVERIZER



- ▶ The special welding process of steel plate greatly improves the welding quality of the jaws.
- ▶ Large flow accelerating valve: Reasonable flow circulation, effectively improves opening and closing efficiency, eliminates pressure peaks, and extends the service life of hydraulic parts.
- ▶ Diversified design of jaw plates maximizes crushing.
- ▶ The movable jaw plate and fixed jaw plate are made of imported HARDOX steel, so the jaw plate is light weight, high strength and strong wear resistance.



TYPE	FP08	FP15	FP20	FP30
A	1370	1670	2025	2525
B	620	750	850	1150
C	125	185	200	240
D	560	630	760	920

Specification	FP08	FP15	FP20	FP30
Max Opening Width	620 mm	750 mm	850 mm	1150 mm
Total Weight	670 kg	1250 kg	1950 kg	3500 kg
Shear Force (average)	885 kN	1650 kN	2330 kN	2870 kN
Crushing Force (end)	390 kN	550 kN	880 kN	1150 kN
Working Pressure	200-300 kg/cm ²	200-300 kg/cm ²	300-350 kg/cm ²	300-350 kg/cm ²
Oil Flow Range	60-120 L/min	140-240 L/min	180-240 L/min	200-250 L/min
Suitable Carrier	7-10 t	11-17 t	18-27 t	28-45 t
Rotation Mode	Fixed	Fixed	Fixed	Fixed